


DOMESTIC GAS THERMOSTATS

REMANUFACTURED REPLACEMENTS FOR ROBERTSHAW "MP" SERIES

THE C1300 MP SERIES THERMOSTATS ARE DESIGNED TO FUNCTION AS LOW-TEMP CONTROLS (140°F TO BROIL). SINCE THIS CONTROL DOES NOT HAVE A GAS COCK AND HAS BEEN KNOWN TO BE INVOLVED IN "RUN-AWAY" SITUATIONS, EXTREME CAUTION SHOULD BE USED IN ITS APPLICATION. A GAS COCK SHOULD ALWAYS BE PLACED ON THE IN-COMING SUPPLY LINE AT THE BACK OF THE RANGE. MANY TIMES THE CONTROL IS RUINED WHEN THE SAFETY VALVE BECOMES DEFECTIVE, CAUSING A "RUN-AWAY", THEREFORE, IT IS A GOOD PRACTICE TO REPLACE BOTH SAFETY (REFER TO REPCO S300 MSA SERIES) AND THERMOSTAT AT THE SAME TIME.

MP	STANDARD. NO SWITCHES OR HEAT MOTORS
MP A-1	WITH "OVEN ON" PANEL LIGHT SWITCH
MP A-3	WITH "OVEN ON" AND "OVEN READY" SWITCH
MP A-4	WITH "OVEN ON" AND "OVEN READY" LIGHT SWITCHES AND LATCHING HEAT MOTOR FOR TIMER
MP A-5	WITH OVEN AND READY LIGHT SWITCHES, RESET TIMER SWITCH, AND NON-LATCHING HEAT MOTOR, NORMALLY USED ON CALORIC AUTO PROBE SYSTEMS
MP A-7	WITH LATCHING HEAT MOTOR FOR TIMER
MP A-9	WITH NON-LATCHING HEAT MOTOR



MODEL MP

MODEL TYPE	TEMP. RANGE	REFERENCE UNI-LINE NUMBER	STOCK NUMBER	STEM			CAP. LGTH	INLET	ADJ. KEYS	COMMENTS
				LGTH	POS.	SIZE				
MP	140°-550°F	4400-020	C1300-001	21/32"	DOWN	11/32"	42"	3/16" TUBE	HEATER	4-WAY DIAL INC.
MP	140°-550°F	4400-019	C1300-002	1 1/8"	UP	1/4"	42"	3/16" TUBE	SEALED	NO DIAL AVAILABLE
MP	140°-550°F	4400-010	C1300-003	¹ 35/64"	DOWN	11/32"	42"	1/8" PIPE	HEATER	4-WAY DIAL INC.
MP	140°-550°F	4400	C1300-MSL	21/32"	DOWN	11/32"	42"	3/16" TUBE	HEATER	
MPA SERIES	140°-550°F	4400	C1370-MSL	21/32"	DOWN	11/32"	42"	3/16" TUBE	HEATER	
MPL SERIES	200°-400°F	4400	C1395-001	21/32"	DOWN	11/32"	42"	3/16" TUBE	SEALED	FRYER APPLICATION

ITEMS THAT WE DO NOT REBUILD:

ANY TYPE OF "SELF-CLEANING" PARTS
TOP BURNER VALVES
ELEMENTS
TIMERS
CLOCKS
MODEL "B" WILCOLATOR